




Top kvalita, velmi dobrá cena, rychlý dodací termín: 4 - 6 týdnů!!!

Premium Metallized Polypropylene Film Capacitors – Axial - JFX

- Passive flammability: GB10191-88 IEC384-16
- Operating temperature: -55°C ~ +85°C
- Capacitance range: 0.047 ~ 100uF
- Capacitance tolerance: ±3%(I), ±5%(J) 1KHz
- Rated voltage: 250V, 400V, 630V.DC
- Withstand voltage: 1.5VR 5S
- Dissipation factor: ≤0.0020 1KHz
- Insulate the electric resistance: >0.33uF ≥15000MΩ
≤0.33uF ≥5000 S
- Leads Diameter: 0,6, 0,8, 1,0, 1,2 Tinned Pure Copper



JFX 1μF 250VDC ±5% Bulk RoHS; **6,9 Kč** / ks při odběru 1000 Ks

JFX 2.2μF 250VDC ±5% Bulk RoHS; **13,8 Kč** / ks při odběru 1000 Ks

SMD Aluminum Electrolytic Capacitor – JCS


- Operating Temperature: -40°C ~ +85°C
- Voltage Range: 4V ~ 100V.DC
- Capacitance Range: 0.1 ~ 470μF
- Capacitance Tolerance: ±20% at 120Hz, 20°C
- Leakage Current Leakage current: (Φ4~Φ8x6.2) ≤0.01CV or 3μA,
whichever is greater.
(after 2 minutes application of rated voltage)



JCS: 10 μF 16V 4x5,4mm ± 20% 2000h při 85°C, RoHS; **0,7 Kč** / ks při odběru 2000 Ks

Axial Met Polyester & Polypropylene Film Capacitor – JFG

- Operating Temperature: -40 ~ +105
- Rated Voltage: 100V, 250V, 400V, 630V.DC
- Withstand Voltage: 1.6V_r 2s (1.5V_r 5s)
- Capacitance Range: 0.033 ~ 68μF
- Capacitance Tolerance: ±5%, ±10%
- Insulation Resistance: C≤0.33μF VR≤100V(10V) ≥7500MΩ
VR>100V ≥15000 MΩ
C>0.33μF VR≤100V(10V) ≥2500S
VR>100V ≥500S
- Dissipation Factor: C<1μF ≤0.013 10KHz
1μF<C≤10μF ≤0.008 1KHz
C>10μF ≤0.010 1KHz



JFGA: 0,47 μF 100VDC 20x7mm ± 10% Bulk RoHS; **2,6 Kč** / ks při odběru 1000 Ks

JFGA: 1 μF 250VDC 25x10mm ± 10% Bulk RoHS; **2,9 Kč** / ks při odběru 1000 Ks

X2 Metallized Polypropylene Film Capacitor – JFO

- Operating Temperature: -40°C ~ +100°C
- Voltage Rating: 300, 280, 275, 250V.AC
- Capacitance Range: 0.001 ~ 2.2μF
- Capacitance Tolerance std: ±10%, ±5%
- Insulation Resistance: 1.R≥30,000MΩ (C≤0.33μF)
1.R≥10,000MΩ (C>0.33μF)
C
- Dissipation Factor: 0.08% max at 1KHz 20°C 0.3% max at 10KHz 20°C
- Dielectric Strength: 1200 VDC for 60 sec.

