

Metallized capacitors


CL21 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.010 to 10
100VDC, 250VDC, 400VDC, 630VDC




CL20 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.010 to 25
100VDC, 250VDC, 400VDC, 630VDC



CL20-1 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.010 to 25
100VDC, 250VDC, 400VDC, 630VDC



MSF Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.0010 to 0.47
63/100VDC, 250VDC, 400VDC, 630VDC



CBB21 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.010 to 3.3
250VDC, 400VDC, 630VDC



CBB13 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.0010 to 0.47
63/100VDC, 250VDC, 400VDC, 630VDC



CBB81 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.0010 to 0.10
1000VDC, 1600VDC, 2000VDC



CL11 Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.0010 to 0.47
100VDC, 250VDC, 400VDC, 630VDC



MSC Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.001 to 1.00
50/63VDC, 100VDC




MEC Series

Temperature range . . . -40°C to +85°C
Capacitance μF 0.01 to 10
50/63VDC, 100VDC




MKP Series

Temperature range . . . -40°C to +100°C
Capacitance μF 0.01 to 2.2



MEK Series


Temperature range . . . MPE -25°C to +70°C
MPP -25°C to +85°C
Capacitance μF 0.5 to 20



Electrolytic Capacitors

EC Series General Purpose Radial 85°C

Temperature range . . . -40°C to +85°C
Capacitance μF 0.1 to 15 000



HT Series High Temperature Radial 105°C

Temperature range . . . -40°C to 105°C
Capacitance μF 0.1 to 15 000



AX Series 105°C Axial Type Capacitors

Temperature range . . . -40°C to +105°C
Capacitance μF 0.47 to 4700



MR Series Miniaturized

Temperature range . . . -40°C to +105°C
Capacitance μF 0.1 to 470



SMR Series Ultra-Mini

Temperature range . . . -40°C to +105°C
Capacitance μF 0.1 to 100



CT Series Chip Electrolytic Capacitors

Temperature range . . . -55°C to +105°C
Capacitance μF 0.1 to 100



LL Series Low Leakage Current

Temperature range . . . -40°C to +105°C
Capacitance μF 0.1 to 1000



NP Series Non-Polar Type

Temperature range . . . -40°C to +105°C
Capacitance μF 0.47 to 1000



