D-SUB SERIES

CHOGORI

D-sub Series Specifications

D-sub Series										
Description		allable,180° inector with			vith Cable, 1 nector with		Front Panel Mount with Female Pin			
Figure										
Drawing										
	39.00 64.00 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7			52.30 • • • • • • • • • • • • • • • • • • •			RL50 Panel Thickness Max. 2.0 mm			
Part-No.	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Part Number		
	9(5A)	4.5-6.5	31009111-01	9(5A)	4.5-8.0	31009113-01-XXX	9(5A)	31009616-01		
	15(2A)	4.5-6.5	31015111-01	15(2A)	4.5-8.0	31015113-01-XXX	15(2A)	31015616-01		
Specifications										
Number of Contacts	9					15				
Wire Gauge	0.3mm ² (22AWG)					0.2mm² (24AWG)				
Cable Range/Panel Thickness		4.5mm -	· 6.5mm	4.5mm - 8.0mm		8.0mm	Max. 2.0mm			
Environmental Protection		IP67								
Mechanical Life	500 mating cycles									
OperatingTemperature	- 45℃ -					- 105°C				
Voltage Rating		90V					90V			
Rated Current (40°C)		5A					2A			