

SA-1W Series

1W Unregulated Single output

Features

- 4 Pin SIL / 8 Pin DIL Package
- 1000 VDC Isolation
- Up to 3000 VDC Isolation
- Low Ripple and Noise
- Efficiency up to 83%
- -40 ~ 85°C Operation Temperature Range
- Non-Conductive Black Plastic Case
- EMI Complies With EN55022 Class B



The SA series is a family of cost effective 1W single output DC-DC converters. These converters achieve low cost and ultra-miniature SIP 4 pin or DIP 8 pin size. Devices are encapsulated using flame retardant resin. The models operate from input voltage of 3.3, 5, 12, 15, 24, 48 Vdc with output voltage of 3.3, 5, 7.2, 9, 12, 15, 18, 24 Vdc. High performance features include 1000Vdc~3000Vdc input/output isolation, high efficiency operation and output voltage accuracy of ±3% maximum. Standard features include an input range of ±10% tolerance and low output noise and ripple.

All specifications typical at Ta=25°C, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS		PHYSICAL SPECIFICATIONS	
Voltage accuracy	±3%	Case Material	Non-conductive Black Plastic(UL94V-0 rated)
Line regulation	±1.2% / Per 1% Vin Change	Pin Material	0.5mm Alloy42 Solder-coated
Load regulation	(From 20% to 100% Load) ±10% (Output 3.3V Model) ±20%	SIP Case	Ø0.5mm Brass Solder-coated
Ripple & noise(20 MHz bandwidth)(1)	100mV pk-pk	Potting Material	Epoxy (UL94V-0 rated)
Temperature coefficient	±0.02%/°C	Weight	(SIP/1.5g) (DIP/1.8g)
Capacitor load(2)	See table	Dimensions	SIP Case 0.46"x0.24"x0.40" DIP Case 0.50"x0.40"x0.27"
INPUT SPECIFICATIONS		ABSOLUTE MAXIMUM RATINGS(4)	
Voltage Range	±10%	These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Max. Input Current	See table	Input Surge Voltage(100mS)	
No-Load Input Current	See table	3.3 Models	6 Vdc ,max.
Input Filter	Capacitors	5 Models	7 Vdc ,max.
Input Reflected Ripple Current(3)	20mA pk-pk	12 Models	15 Vdc ,max.
ENVIRONMENT SPECIFICATIONS		15 Models	18 Vdc ,max.
Operating Temperature	-40°C~85°C(See Derating Curve)	24 Models	28 Vdc ,max.
Maximum Case Temperature	100°C	48 Models(for SIP)	54 Vdc ,max.
Storage Temperature	-40°C~125°C	Soldering Temperature (1.5mm from case 10sec. max.)	
Cooling	Nature Convection	260°C ,max.	
GENERAL SPECIFICATIONS		EMC SPECIFICATIONS	
Efficiency	See table	Radiated Emissions	EN55022 CLASS B
I/O Isolation Voltage(3 sec) Input/Output	1000~3000Vdc	Conducted Emissions (6)	EN55022 CLASS B
I/O Isolation Capacitance	60 pF Typ.	ESD	IEC 61000-4-2 Perf. Criteria A
I/O Isolation Resistance	1000M Ohm	RS	IEC 61000-4-3 Perf. Criteria A
Switching Frequency	Variable 80kHz	EFT (7)	IEC 61000-4-4 Perf. Criteria A
Humidity	95% rel H	Surge (7)	IEC 61000-4-5 Perf. Criteria A
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121Mhrs	CS	IEC 61000-4-6 Perf. Criteria A
Safety Standard : (designed to meet)	IEC 60950-1	PFMF	IEC 61000-4-8 Perf. Criteria A

SA - 1W Unregulated Single output

PARTNUMBER STRUCTURE

SA - 1205S1H

- Series Name:** SA
- Input Voltage:** 3R3 - 3.3V
05 - 5V
12 - 12V
15 - 15V
24 - 24V
48 - 48V(for SIP)
- Output Voltage:** 3R3 - 3.3V
05 - 5V
09 - 9V
12 - 12V
15 - 15V
18 - 18V
24 - 24V
- Case Type:** S - SIP Case
D - DIP Case
- Power Rating:** 1W
- Isolation:** 3KVDC Isolation
Optional, if no suffix "H" mean 1 KVDC Isolation

Derating Curve

The graph shows Output Power (Y-axis, 25% to 100%) versus Ambient Temperature (X-axis, -40°C to 120°C). A green shaded region represents the Safe Operating Area (SOA), which is constant at 100% power until an ambient temperature of 85°C, after which it decreases linearly to 0% power at 100°C. The text "S.O.A." is overlaid on the green area.

MODEL SELECTION GUIDE

Model Number	Input Voltage Range (Vdc)	Input Current		Output Voltage (Vdc)	Output Current	Efficiency @FL (%)	Capacitor Load (uF)
		No-Load (mA)	Full Load (mA)				
SA-3R33R3S1	3.3	25	421	3.3	303	72	220
SA-3R305S1	3.3	25	394	5	200	77	220
SA-3R37R2S1	3.3	25	384	7.2	139	79	220
SA-3R309S1	3.3	30	404	9	111	75	220
SA-3R312S1	3.3	45	473	12	100	77	220
SA-3R315S1	3.3	35	384	15	67	79	220
SA-3R318S1	3.3	35	399	18	56	76	220
SA-3R324S1	3.3	53	461	24	50	79	220
SA-053R3S1	5	20	257	3.3	303	78	220
SA-0505S1	5	25	247	5	200	81	220
SA-057R2S1	5	16	241	7.2	139	83	220
SA-0509S1	5	26	250	9	111	80	220
SA-0512S1	5	25	300	12	100	80	220
SA-0515S1	5	35	244	15	67	82	220
SA-0518S1	5	25	247	18	56	81	220
SA-0524S1	5	35	289	24	50	83	220
SA-123R3S1	12	15	107	3.3	303	78	220
SA-1205S1	12	16	105	5	200	79	220
SA-127R2S1	12	16	100	7.2	139	83	220
SA-1209S1	12	15	107	9	111	78	220
SA-1212S1	12	20	125	12	100	80	220
SA-1215S1	12	15	105	15	67	79	220
SA-1218S1	12	20	104	18	56	80	220
SA-1224S1	12	25	123	24	50	81	220
SA-153R3S1	15	15	89	3.3	303	75	220
SA-1505S1	15	9	82	5	200	81	220
SA-157R2S1	15	12	88	7.2	139	76	220
SA-1509S1	15	10	90	9	111	74	220
SA-1512S1	15	13	100	12	100	80	220
SA-1515S1	15	15	84	15	67	79	220
SA-1518S1	15	12	85	18	56	78	220
SA-1524S1	15	10	99	24	50	81	220

Suffix "H" means 3 KVdc isolation

SA - 1W Unregulated Single output

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current Full load (mA)	EFFICIENCY @FL (%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)				
SA-243R3S1	24	8	54	3.3	303	77	220
SA-2405S1	24	8	52	5	200	80	220
SA-247R2S1	24	10	54	7.2	139	77	220
SA-2409S1	24	7	54	9	111	77	220
SA-2412S1	24	8	62	12	100	80	220
SA-2415S1	24	8	51	15	67	81	220
SA-2418S1	24	8	52	18	56	80	220
SA-2424S1	24	9	60	24	50	83	220
SA-483R3S1	48	6	29	3.3	303	73	220
SA-4805S1	48	6	28	5	200	74	220
SA-487R2S1	48	7	27	7.2	139	77	220
SA-4809S1	48	5	27	9	111	78	220
SA-4812S1	48	5	32	12	100	77	220
SA-4815S1	48	5	27	15	67	76	220
SA-4818S1	48	8	28	18	56	75	220
SA-4824S1	48	8	31	24	50	80	220
SA-3R3 3R3D1	3.3	25	410	3.3	303	74	220
SA-3R3 05D1	3.3	25	394	5	200	77	220
SA-3R3 7R2D1	3.3	30	404	7.2	139	75	220
SA-3R3 09D1	3.3	30	399	9	111	76	220
SA-3R3 12D1	3.3	45	485	12	100	75	220
SA-3R3 15D1	3.3	25	384	15	67	79	220
SA-3R3 18S1	3.3	35	399	18	56	76	220
SA-3R3 24D1	3.3	90	485	24	50	75	220
SA-05 3R3D1	5	16	256	3.3	303	78	220
SA-05 05D1	5	15	253	5	200	79	220
SA-05 7R2D1	5	16	241	7.2	139	83	220
SA-05 09D1	5	25	253	9	111	79	220
SA-05 12D1	5	25	296	12	100	81	220
SA-05 15D1	5	25	244	15	67	82	220
SA-05 18D1	5	25	241	18	56	83	220
SA-05 24D1	5	28	293	24	50	82	220
SA-12 3R3D1	12	15	108	3.3	303	77	220
SA-12 05D1	12	16	105	5	200	79	220
SA-12 7R2D1	12	16	100	7.2	139	83	220
SA-12 09D1	12	15	105	9	111	79	220
SA-12 12D1	12	20	125	12	100	80	220
SA-12 15D1	12	17	105	15	67	79	220
SA-12 18D1	12	15	103	18	56	81	220
SA-12 24D1	12	25	127	24	50	79	220
SA-15 3R3D1	15	15	89	3.3	303	75	220
SA-15 05D1	15	10	83	5	200	80	220
SA-15 7R2D1	15	12	88	7.2	139	76	220
SA-15 09D1	15	10	85	9	111	78	220
SA-15 12D1	15	13	98	12	100	82	220
SA-15 15D1	15	15	83	15	67	80	220
SA-15 18D1	15	12	85	18	56	78	220
SA-15 24D1	15	10	99	24	50	81	220

Suffix "H" means 3 KVdc isolation

SA - 1W Unregulated Single output


MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current Full load (mA)	EFFICIENCY @FL (%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)				
SA-24 3R3D1	24	8	53	3.3	303	79	220
SA-24 05D1	24	8	53	5	200	79	220
SA-24 7R2D1	24	10	56	7.2	139	74	220
SA-24 09D1	24	7	53	9	111	79	220
SA-24 12D1	24	8	63	12	100	80	220
SA-24 15D1	24	8	52	15	67	80	220
SA-24 18D1	24	8	51	18	56	82	220
SA-24 24D1	24	9	61	24	50	82	220

Suffix "H" means 3 KVdc isolation

TEST CONFIGURATIONS


Input Reflected Ripple Current Test Step

Input reflected ripple current is measured through a source inductor Lin(12uH) and a source capacitor Cin(47uF, ESR<1.0Ω at 100KHz) at nominal input and full load.



Output Ripple & Noise Measurement Test


The Scope measurement bandwidth is 20MHz .



EMI Filter

Input filter components (C1 , L , C2 , C3) are used to help meet conducted emissions requirement for the module.

These components should be mounted as close as possible to the module; and all leads should be minimized to decrease radiated noise.




	C1	L	C2	C3
SA-3R3XXXXX	1210, 2.2uF/100V	18uH		
SA-05XXXXXX	1210, 2.2uF/100V	18uH		
SA-12XXXXXX	1210, 2.2uF/100V	18uH		
SA-15XXXXXX	1210, 2.2uF/100V	18uH		
SA-24XXXXXX	1210, 2.2uF/100V	18uH	1210, 2.2uF/100V	1206, 470pF/2KV
SA-48XXXXXX	Electrolytic capacitor, 10uF/100V	18uH	1210, 2.2uF/100V	1206, 470pF/2KV


NOTE

- 1.Ripple/Noise measured with 20MHz bandwidth.
- 2.Tested by minimal Vin and constant resistive load.
- 3.Measured Input reflected ripple current with a simulated source inductance of 12uH.
- 4.Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.
- 5.Operation under no-load conditions will not damage these devices, however they may not meet all listed specifications.
6. Input filter components are required to help meet conducted emission class B, which application refer to the EMI Filter of design & feature configuration.
7. An external filter capacitor is required if the module has to meet IEC61000-4-4 and IEC61000-4-5.
The filter capacitor Schmid-M suggest: Nippon - chemi - con KY series, 470uF/100V.


SA - 1W Unregulated Single output




05 Models



12 Models




24 Models



48 Models

MECHANICAL SPECIFICATIONS




4 Pin SIL Package

Notes : All dimensions are typical in millimeters (inches).
 1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
 2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
 3. Case Tolerance: ± 0.5 (± 0.02)

* The thickness of 48V input voltage model is 7.50(0.29)

PIN CONNECTIONS	
PIN NUMBER	SINGLE
1	-V Input
2	+V Input
3	-V Output
4	+V Output

(The Pin Connection of high isolation one is the same with normal one.)



8 Pin DIL Package

Notes : All dimensions are typical in millimeters (inches).
 1. Pin diameter: 0.5 ± 0.05 (0.02 ± 0.002)
 2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
 3. Case Tolerance: ± 0.5 (± 0.02)

PIN CONNECTIONS	
PIN NUMBER	SINGLE
1	-V Input
4	+V Input
5	+V Output
7	-V Output

(The Pin Connection of high isolation one is the same with normal one.)