

Picture	Type	Size	Frequency Range	S/N ratio	Sensitivity (0dB=1v/Pa 1000Hz)	Directivity	Impedance	Current Consumption	Description
	SM M1508	15x8.0mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	1.5v condenser microphone for telephone
	SM M1465UL-12H-GP	17x6.5mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	14mm Electret Condenser Uni-direction Element
	SM M1606	16x6mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	16mm electret condenser microphone
	SM M4015PR	4.0x1.5mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	4*1.5mm Electret Condenser Microphone with rubber
	SM M4015WW	4.0x1.5mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	Super Mini High Sensitivity Electret Condenser Microphone with Wire
	SM6022P	6.0x2.2mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	6*2.2mm Omnidirectional Electret Condenser microphone with pin
	SM M6027	6.0x2.7mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	6*2.7mm 48db Electret Condenser Microphone without pin
	SM M6027P	6.0x2.7mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	58db 6*2.7mm Electret Condenser Microphone with pin
	SM M6050	6.0x5.0mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	two planes of the capacitor 6mm electret condenser microphone
	SM M6050P	6.0x5.0mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	two planes of the capacitor 6mm electret condenser microphone
	SM M9745	9.7x4.5mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	9.7mm*4.5mm Noise canceling electret condenser microphone
	SM M9745P	9.7x4.5mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	9.7*4.5mm High Sensitivity Electret Condenser Microphone with pin
	SM M9750N	9.7x5.0mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	60db Electret Omnidirectional Condenser Microphone
	SM M9767	9.7x6.7mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	9767 Microphone Anti-interference MIC with pin
	SM M9767P	9.7x6.7mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	9.7*6.7mm 38dB Omnidirectional Electret Condenser microphone
	SM M SMD3015-3P	4.0x1.2mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	mic capsule electret condenser pickup microphone 52db
	SM M SMD4013-3P	4.0x1.2mm	50~20KHz	> 58dB	-48~66dB	Omni Directional	Max2.2KΩ at f=1KHz	> 500uA	Omnidirectional electret condenser microphone capsule