




# STANDARD SERIES

## CHOGORI

### Standard Series Specifications

#### Standard series, Male connector & Male Pin

Description	Molded with Cable, 90° Screw Type, Solder	Molded with Cable, 90° Lock Bayonet Type, Solder	Molded with Cable, 90° Push Lock Type, Solder
Figure			

Drawing			
---------	---	---	---

Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number
		2	Max. 9.0	22002114-01-XXX 	2	Max. 9.0	22002124-01-XXX 	2	Max. 9.0
	3	2200311401-XXX 		3	22003124-01-XXX 		3	22003134-01-XXX 	
	4	22004114-01-XXX 		4	22004124-01-XXX 		4	22004134-01-XXX 	
	5	22005114-01-XXX 		5	22005124-01-XXX 		5	22005134-01-XXX 	
	6	22006114-01-XXX 		6	22006124-01-XXX 		6	22006134-01-XXX 	
	2+4	22204114-01-XXX		2+4	22204124-01-XXX		2+4	22204134-01-XXX	
	2+6	22206114-01-XXX		2+6	22206124-01-XXX		2+6	22206134-01-XXX	

#### Specifications

Number of Contacts	2	3	4	5	6	2+4	2+6
Wire Gauge	0.823mm <sup>2</sup> (18AWG)			0.519mm <sup>2</sup> (20AWG)		0.823mm <sup>2</sup> (18AWG)*2C 0.34mm <sup>2</sup> (22AWG)*4C	
Cable Range	Max. 9.0 mm						
Environmental Protection	IP67			IP67			IP67
Mechanical Life	500 mating cycles						
Operating Temperature	- 40°C - 80°C						
Voltage Rating	300V	300V	125V	60V	60V	60V	30V
Rated Current (40°C)	10A	10A	10A	5A	5A	10A+2A	5A+2A