




MIDDLE SERIES

CHOGORI

Middle Series Specifications

Middle Series, Front Panel Mount & Female Pin

Description	Front Panel Mount Screw Type, PCB	Front Panel Mount Lock Bayonet Type, PCB	Front Panel Mount Push Lock Type, PCB
Figure			

Drawing		Note: 9.10 positions, L=17.0 other positions, L=18.0 	
---------	---	--	---

Part-No.	Screw Type		Lock Bayonet Type		Push Lock Type	
	Contacts	Part-Number	Contacts	Part-Number	Contacts	Part-Number
	2	23002615-02	2	23002625-02	2	23002635-02
	3	23003615-02	3	23003625-02	3	23003635-02
	4	23004615-02	4	23004625-02	4	23004635-02
	5	23005615-02	5	23005625-02	5	23005635-02
	6	23006615-02	6	23006625-02	6	23006635-02
	7	23007615-02	7	23007625-02	7	23007635-02
	8	23008615-02	8	23008625-02	8	23008635-02
	3+5	23305615-02	3+5	23305625-02	3+5	23305635-02
	9	23009615-02	9	23009625-02	9	23009635-02
	10	23010615-02	10	23010625-02	10	23010635-02
	12	23012615-02	12	23012625-02	12	23012635-02
	14	23014615-02	14	23014625-02	14	23014635-02
	18	23018615-02	18	23018625-02	18	23018635-02

Specifications													
Number of Contacts	2	3	4	5	6	7	8	3+5	9	10	12	14	18
Wire Gauge	2.5mm ² (14AWG)		1.0mm ² (17AWG)	0.75mm ² (18AWG)		0.34mm ² (22AWG)		1.0mm ² +0.25mm ² (17AWG +24AWG)	0.34mm ² (22AWG)	0.25mm ² (24AWG)			
Panel Thickness	Max. 4.0mm					Max. 4.0mm			Max. 2.5mm				
Environmental Protection	IP68					IP67			IP67				
Mechanical Life	500 mating cycles												
Operating Temperature	- 45°C - 105°C												
Voltage Rating	300V	300V	300V	125V	125V	60V	60V	125+30V	60V	30V	30V	30V	30V
Rated Current(40°C)	20A	20A	15A	10A	10A	5A	5A	15A+2A	5A	5A	2A	2A	2A